


Engineered Products (cont.)

Pipe Driver (Bore Driver)

- · Full turning or grinding without unchucking
- · Blades index in the event or scoring, doubling blade life
- · Replacement blades are interchangeable within .005"
- · Blades can be replaced or indexed without removing from machine
- Retainer lugs and slot depth provide excellent stiffness and rigidity under extreme feeds and speeds
- Torque limit on straight shanks prevents driver from slipping at breakaway/startup
- Crowned angles and flats designed to minimize impressions in bevels
- Material selection and heat treating are carefully monitored to
 maximize performance under demanding production conditions









| PIPE DRIVER | | | | |
|-------------|-------|-------|------------------|--|
| Model | А | F | No. of Blades | |
| PD045 | 4.50 | 1.50 | 3 | |
| PD075 | 7.50 | 4.50 | 5 | |
| PD105 | 10.50 | 7.50 | 7 | |
| PD135 | 13.50 | 10.50 | 9 | |

Pipe Driver comes with two sets of crowned blades.

| BLADES | | | |
|--------|-------------|--|--|
| Model | Blade Style | | |
| BS100 | Square | | |
| BC100 | Crowned | | |

Spider Mandrels (Live or Dead)

- Precision incremental adjustments in thin wall bores
- Rotational accuracy of mandrels is .0002"
- Available with 3, 4, and 6
 adjustment lugs
- Design of mandrel provides easy access to adjustment lugs
- Optional materials available for special design lugs
- Bull rings with extended lugs available to accommodate larger bores without changing the mandrel





Call 1-800-338-0027