



# Hydraulic Face Drivers (Cont.)



(See page 68 for component selection and ordering information.)

## TYPE 63: Driving Diameter Range: 1.44" - 2.38"

#1 FACE DRIVER								
Order Code	Mounting Style	Max. Part Weight	Order Code	Mounting Style	Max. Part Weight	Order Code	Mounting Style	Max. Part Weight
6305	#5 Morse Taper	160 lbs.	63C1	Chuck Mount	160 lbs.	63F1	Flange Mount	160 lbs.
6306	#6 Morse Taper	160 lbs.	63C2	Chuck Mount H.D.	220 lbs.	63F2	Flange Mount H.D.	220 lbs.
			63C3	Chuck Mount H.D.	560 lbs.	63F3	Flange Mount H.D.	560 lbs.
			63C4	Chuck Mount H.D.	1000 lbs.	63F4	Flange Mount H.D.	1000 lbs.

#2 CENTER POINT	
Order Code	Center Hole Dia. Range
C6301	0.393 - 0.511
C6302	0.511 - 0.629
C6303	0.629 - 0.748
C6304	0.748 - 0.866
C6305	0.866 - 0.984
C6306	0.984 - 1.102
C6307	1.102 - 1.220
C6308	1.220 - 1.338
C6309	1.338 - 1.456
C6310	1.456 - 1.574

#3 DRIVE PINS (5 pins required)				
Order Code	Counterclockwise (Right)		Clockwise (Left)	
	Outer Driving Diameter	Inner Driving Diameter	Outer Driving Diameter	Inner Driving Diameter
P6401	1.44	1.08	2.38	2.02
P6402	2.38	2.02	1.44	1.08
P6403	1.73	1.08	2.38	1.73
P6404	2.38	1.73	1.73	1.08
P6405	1.97	1.45	1.97	1.45
P6406	2.38	1.08	2.38	1.08

#4 SPINDLE ADAPTER (For direct mount only)	
Order Code	Spindle Size
705050	A2-6
705051	A2-8
705052	A2-11

## TYPE 64: Driving Diameter Range: 1.95" - 2.89"

#1 FACE DRIVER								
Order Code	Mounting Style	Max. Part Weight	Order Code	Mounting Style	Max. Part Weight	Order Code	Mounting Style	Max. Part Weight
6405	#5 Morse Taper	160 lbs.	64C2	Chuck Mount H.D.	220 lbs.	64F1	Flange Mount H.D.	160 lbs.
6406	#6 Morse Taper	160 lbs.	64C3	Chuck Mount H.D.	560 lbs.	64F2	Flange Mount H.D.	220 lbs.
64C1	Chuck Mount	160 lbs.	64C4	Chuck Mount H.D.	1000 lbs.	64F3	Flange Mount H.D.	560 lbs.

#2 CENTER POINT	
Order Code	Center Hole Dia. Range
C5501	0.393 - 0.590
C5502	0.590 - 0.787
C5503	0.787 - 0.984
C5504	0.984 - 1.181
C5505	1.181 - 1.378
C6401	1.378 - 1.575
C6402	1.575 - 1.772
C6403	1.772 - 1.969
C6404	1.969 - 2.166
C6405	2.166 - 2.363

#3 DRIVE PINS (6 pins required)				
Order Code	Counterclockwise (Right)		Clockwise (Left)	
	Outer Driving Diameter	Inner Driving Diameter	Outer Driving Diameter	Inner Driving Diameter
P6401	1.95	1.59	2.89	2.53
P6402	2.89	2.53	1.95	1.59
P6403	2.24	1.59	2.89	2.24
P6404	2.89	2.24	2.24	1.59
P6405	2.48	1.96	2.48	1.96
P6406	2.89	1.59	2.89	1.59

#4 SPINDLE ADAPTER (For direct mount only)	
Order Code	Spindle Size
705050	A2-6
705051	A2-8
705052	A2-11